

STAIRWELL ACCESS UNIT

For safe access on both industrial and domestic stairwells.

The basic stairwell pack provides a platform level of 2.7m from the lowest step.

The unit is 0.7m wide, and features special narrow base plates, adjustable legs and non-slip platform boards.

Easy access from both sides of the stairwell unit to the platform is provided by a walk through ladder frame. Simply walk through the frame and climb the ladder.

This frame design solves the access problems experienced on narrow and domestic staircases.

Integrated access frame so access on the staircase can still be obtained.

Optional Extra's Include:

- Extension pack to raise the platform level from 2.7m to 4.20m from the lowest step
- Aluminium Toeboard assembly
- Additional side props for extra support on narrow applications

EURO TOWERS LTD
MANUFACTURERS OF ALUMINIUM ACCESS EQUIPMENT

Unit 5 Edgemoad Close, Round Spinney, Northampton NN3 8RG
Call: 01604 644 774 Email: sales@eurotowers.co.uk

STAIRWELL ACCESS UNIT

Assembly Instructions

Ensure all parts are present and are not damaged before assembling

Stairwell Basic Unit

Comprising of...

- 4 x SWAL - Stairwell Adjustable leg
- 2 x SWAF - Stairwell access frames
- 1 x SWPF - Stairwell plain frame
- 2 x SWDB - Stairwell diagonal brace
- 5 x SWHB - Stairwell horizontal brace
- 1 x SWTP - Stairwell trapdoor platform
- 1 x SWSG - Stairwell short guardrail frame
- 1 x SWTG - Stairwell tall guardrail frame
- 1 x SWTB - Stairwell Toeboard assembly

STEP 1

Insert adjustable legs into frames



STEP 2

Fit horizontal brace above designated locating collar, level tower by using the adjustable legs. Fit lower diagonal brace as shown



STEP 3

Add plain frames with short guard rail attached and engage interlock clips. Fit upper diagonal brace.



STEP 4

Position the platform with the trapdoor to the front.



STEP 5

From the stairs fit tall guardrail frame.



STEP 6

Sit through the trap and fit four horizontal braces using the 3T method creating the guardrail, fit toe boards.

STEP 7

Dismantling is the reverse of assembly.

For more information on this unit or the Stairwell Extension pack, please contact us on **01604 644 774** or sales@eurotowers.co.uk



LENGTH: 1.5/
WIDTH: 0.70
PLATFORM LEVEL: 2.7M
(From lowest step)

General Safety Rules:

1. Do not use if the product is damaged or has parts missing
2. Do not use on unstable ground such as loose bricks, boxes or blocks.
3. Before use ensure that the base plates are fully fitted to the frame, tighten if necessary.
4. Remove all personnel and materials before moving the unit.
5. Do not gain extra height by using boxes, ladders etc on the platform.
6. Ensure that the locking hooks on platforms are functioning correctly.
7. Ensure that the frame interlock clips are properly fitted.
8. If there is an overhead hazard use head protection.
9. Never gain entrance to the platform by climbing over the outside of the unit.
10. Do not over load the unit.

**MAX SAFE WORKING LOAD FOR PLATFORM /
STRUCTURE 150KG**

EURO TOWERS LTD
MANUFACTURERS OF ALUMINIUM ACCESS EQUIPMENT

Unit 5 Edgemead Close, Round Spinney, Northampton NN3 8RG
Call: 01604 644 774 Email: sales@eurotowers.co.uk